



Location:



4-236  
Clear-flo Brass Showerhead  
**Specification Submittal**



Model Numbers	Feature Highlights
<input type="checkbox"/> <b>4-236</b> Clear-flo Brass Showerhead	<ul style="list-style-type: none"><li>• Female ball joint connection</li><li>• Standard flow rate is 2.0 gpm (7.6 L/min)</li><li>• Polished Chrome finish</li></ul>
Options/ Modifications	
<input type="checkbox"/> <b>1.5</b> 1.5 (5.7 L/min) Flow rate restrictor	
<input type="checkbox"/> <b>STN</b> Satin Nickel finish	
<input type="checkbox"/> <b>304</b> With 304 Head Bracket	
<p><b>Note:</b> Append appropriate -suffix to model number.</p>	
Compliance	Warranty
<p>- ASME A112.18.1/CSA B125.1</p> 	<p><b>Limited Lifetime</b> - to the original end purchaser in consumer/residential installations.</p> <p><b>10 Years</b> - for commercial/industrial installations. Refer to <a href="http://www.symmons.com/warranty">www.symmons.com/warranty</a> for complete warranty information.</p> 

**Architectural/ Engineering Specification**

Symmons Clear-flo Brass Showerhead \_\_\_\_\_ Includes Female ball joint connection, Standard flow rate is 2.0 gpm (7.6 L/min), Polished Chrome finish. 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant. Available options: "1.5 - 1.5 (5.7 L/min) Flow rate restrictor", "STN - Satin Nickel finish", "304 - With 304 Head Bracket".

---

**Dimensions**

---

