




1-25VT-FS  
Hand Shower System  
**Specification Submittal**

Location:

Model Numbers	Options/Modifications
<input type="checkbox"/> <b>1-25VT-FS</b> Hand Shower System with Symmons Visu-Temp® pressure-balancing mixing valve	<input type="checkbox"/> <b>-X</b> Symmons temptrol mixing valve includes integral service stops to allow water shut-off for service  <input type="checkbox"/> <b>-CHKS</b> Integral check stops - for use in installations where a positive shutt-off device is used downstream, of mising valve  <input type="checkbox"/> <b>-1.5</b> 1.5 gpm (5.7 L/min) flow rate restrictor (Requires substituting hand shower wand with #EF-100)  <input type="checkbox"/> <b>-72</b> 6 foot hand shower hose in place of standard 5 foot hose  <input type="checkbox"/> <b>-R</b> Vinyl hose in place of flexible metal hose
<b>Feature Highlights</b> <ul style="list-style-type: none"> <li>• Symmons Visu-Temp® pressure-balancing mixing valve with Clear-vue™ thermometer and adjustable stop screw to limit handle turn, #VT-1.</li> <li>• Euro-flo single mode wall/hand shower with flexible metal hose, in-line vacuum breaker, wall connection and flange, #FS-KIT that includes wand #460C.</li> <li>• Standard flow rate is 2.0 gpm (7.6 L/min).</li> <li>• Polished Chrome finish (standard).</li> <li>• When vacuum breaker is required order EF-109.</li> </ul>	
<b>Compliance</b> <ul style="list-style-type: none"> <li>• ASME A112.18.1/CSA B125.1.</li> <li>• Lever handle meet ADA requirements for operation.</li> </ul>  	
<b>Warranty</b>  <b>Limited Lifetime</b> - for residential installations. <b>10 Years</b> - for commercial/industrial installations. Refer to <a href="http://www.symmons.com/warranty">www.symmons.com/warranty</a> for complete warranty information. 	
<p><b>Note:</b> Append appropriate -suffix to model number.</p>	

### Architectural/Engineering Specification

Symmons Visu-Temp® Hand Shower System \_\_\_\_\_ Includes Symmons Visu-Temp® pressure-balancing mixing valve with Clear-vue™ thermometer and adjustable stop screw to limit handle turn, #VT-1, Euro-flo single mode wall/hand shower with flexible metal hose, in-line vacuum breaker, wall connection and flange, #FS-KIT that includes wand #460C, Standard flow rate is 2.0 gpm (7.6 L/min), and Polished Chrome finish (standard). When vacuum breaker is required order EF-109. 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant and lever handle meet ADA requirements for operation. Available options: X = Integral service stops, CHKS = Integral Check Stops, 1.5 = 1.5 gpm (5.7 L/min) flow restrictor, 72 = 6 foot hose, and R = Vinyl hose.

## Dimensions

Male 1/2" I.P.S. thread must protrude 3/8" (10mm) from finished wall for proper installation of street ell and flange.

