




Location:



**1-1170VT-H401-V  
Visu-Temp® Shower/Hand Shower System  
Specification Submittal**



Model Numbers	Feature Highlights
<input type="checkbox"/> <b>1-1170VT-H401-V</b> Visu-Temp® Shower/Hand Shower System	<ul style="list-style-type: none"> <li>▪ Symmons Visu-Temp® pressure-balancing mixing valve with Clear-vue™ thermometer and adjustable stop screw to limit handle turn, #4-5000VT.</li> <li>▪ Euro-flo single mode wall/hand shower with flexible metal hose, wall connection, flange and cradle for mounting hand shower, #H401-V that includes wand #EF-118</li> <li>▪ Lever diverter, 2DIV-BODY with volume control for showerhead and hand shower</li> <li>▪ Euro-flo single mode self-cleaning showerhead #4-241</li> <li>▪ Showerhead mounting arm and flange, # 300</li> <li>▪ Standard flow rate is 2.0 gpm (7.6 L/min) Optional aerator available in lower flow rates</li> <li>▪ Polished chrome finish (standard)</li> <li>▪ For optional in-line vacuum breaker order p/n EF-109</li> </ul>
<p><b>Options/ Modifications</b></p> <input type="checkbox"/> <b>-TRM</b> Trim only, valve body ordered separately <input type="checkbox"/> <b>-X</b> Symmons Temptrol® pressure balancing mixing valve includes integral service stops to allow water shut-off for service <input type="checkbox"/> <b>-X-CHKS</b> Integral check stops: Used where a positive shut-off device is used down stream of mixing valve <input type="checkbox"/> <b>-X-3/4</b> 3/4 inch valve to increase water flow approximately 20% <input type="checkbox"/> <b>-72</b> Includes 72" hose <input type="checkbox"/> <b>-NS</b> Non-shared diverter valve <input type="checkbox"/> <b>-1.5</b> 1.5 gpm (5.7 L/min) flow rate restrictor <input type="checkbox"/> <b>L1</b> Less showerhead <input type="checkbox"/> <b>L2</b> Less hand shower <input type="checkbox"/> <b>L3</b> Less showerhead and hand shower <input type="checkbox"/> <b>L4</b> Less showerhead, arm, and flange <input type="checkbox"/> <b>L5</b> Less hand shower system <input type="checkbox"/> <b>STN</b> Satin Nick Finish <p><b>Note:</b> -Append appropriate -suffix to model number.            -When ordering L1-L7 modifiers, remove hyphens from model number.</p>	
<p><b>Compliance</b></p> <p>- ASME A112.18.1/CSA B125.1</p> 	<p><b>Warranty</b></p> <p><b>Limited Lifetime</b> - to the original end purchaser in consumer/residential installations.  <b>10 Years</b> - for commercial/industrial installations. Refer to <a href="http://www.symmons.com/warranty">www.symmons.com/warranty</a> for complete warranty information.</p> 

**Architectural/ Engineering Specification**

Symmons Visu-Temp Shower and Hand Shower System \_\_\_\_\_ Includes Visu-Temp Pressure-Balancing mixing valve with Clear-Vue™ thermometer, Adjustable stop screw to limit handle turn, Lever diverter with volume control for shower head and hand shower, Single mode showerhead with arm and flange, Single mode wall/hand shower with flexible 5' metal hose, Dual checks for backflow protection, Wall connection and flange, Cradle for hand shower mounting, Standard flow rate 2.0 gpm (7.6 L/min). 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant. Available options: "1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "STN - Satin Nickel finish", "X - Integral service stops—allows water shut-off at valve for service", "X-3/4 - 3/4" valve to increase flow approximately 20%", "X-CHKS - Integral check stops—for use in installations where a positive shut-off device is used downstream of mixing valve", "NS - Non-shared diverter valve", "TRM - Trim only", "L1 - Less handle", "L2 - Less hand shower", "L3 - Less showerhead and hand shower", "L4 - Less showerhead, arm, & flange", "L5 - Less hand shower system".

## Dimensions

### Dimensions Visu-Temp Shower System with Hand Shower, 1-1170VT-H401-V

