



Location:



1-25-FSB
HAND SHOWER SYSTEM
Specification Submittal

Model Numbers	Feature Highlights
<input type="checkbox"/> 1-25-FSB Hand shower system with 30 inch adjustable slide bar, Safetymix 3-port pressure balancing mixing valve#4-500	<ul style="list-style-type: none"> ▪ Symmons Safetymix 3-port pressure balancing mixing valve with lever handle and adjustable stop screw to limit handle turn. ▪ Open Flow FS hand shower with 5 foot flexible metal hose, dual checks for backflow protection, wall connection and flange ▪ 30 inch adjustable slide bar for mounting hand shower ▪ Standard flow rate 2.0 gpm (7.6 L/min) Optional lower flow rate restrictor available ▪ Polished chrome finish ▪ For optional in-line vacuum breaker order p/n EF-109
Options/ Modifications	
<input type="checkbox"/> 1.5 <i>1.5 gpm (5.7 L/min) flow restrictor</i> <input type="checkbox"/> L2 <i>Less hand shower (wand only)</i> <input type="checkbox"/> L5 <i>Less hand shower system (less bar/cradle, hose, wand & elbow)</i> <input type="checkbox"/> L7 <i>Less handle</i> <input type="checkbox"/> BX <i>Back connection with integral stops</i> <input type="checkbox"/> G <i>Dial thermometer</i> <input type="checkbox"/> VP <i>Vandal resistant escutcheon screws in place of standard screws</i> <input type="checkbox"/> X <i>Integral stops - allows water shut off at valve for service. Recommended for use on all multiple commercial installations</i> <input type="checkbox"/> X-3/4 <i>3/4" valve to increase flow approximately 20%</i> <input type="checkbox"/> X-CHKS <i>Integral check stops - for use in installations where a positive shut-off device is used downstream of mixing valve</i>	<h3>Warranty</h3> <p>Limited Lifetime - to the original end purchaser in consumer/residential installations.</p> <p>10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.</p> 
<p>Note: Append appropriate suffix to model number.</p>	<h3>Compliance</h3> <p>- ASME A112.18.2-2020/CSA B125.2-20</p> 

Architectural/ Engineering Specification

Symmons _____ HAND SHOWER SYSTEM. Includes Safetymix 3-port pressure balancing mixing valve with lever handle and adjustable screw stop to limit handle turn, Open Flow FS hand shower with 5 foot flexible metal hose, dual checks for backflow protection, wall connection and flange, 30 inch adjustable slide bar for mounting hand shower, standard flow rate 2.0 gpm (7.6 L/min), and polished chrome finish. 10 Year Commercial Warranty. ASME A112.18.2/CSA B125.2 compliant. Available options: "1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "L2 - Less hand shower (wand only)", "L5 - Less hand shower system (less bar/cradle, hose, wand and elbow)", "L7 - Less handle", "BX - back connection with integral stops", "G - Dial thermometer", "VP - Vandal resistant eschusteon screw in place of stant screws", "X - Integral stops", "X-3/4 - 3/4" valve to increse flow approximateliy 20%", "X-CHKS - Integral check stops".



1-25-FSB

Dimensions

