

Location:

# SYMMONS® Symmetrix®

## Tub-Shower System S-2002

### Specification Submittal



#### Feature Highlights

- Symmons Tub-Shower System with LR style lever handle
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit temperature adjust handle turn and a secondary integral diverter with lever handle for selecting between tub and shower
- Showerhead #4-141 single mode with adjustable flood or mist spray
- Showerhead mounting arm and flange
- Flow rate 2.5 gpm (9.5 L/min)  
*Optional lower flow rate restrictor available*
- Open flow 5-1/4" zinc tub spout, #060
- Polished chrome finish (standard)

#### Model Numbers

- S-2002..... Tub-Shower System with Symmons Temptrol® mixing valve p/n S-86-2-BODY
- S-2002-TRM..... Trim only, valve must be ordered separately
- S-86-2-BODY..... Symmons Temptrol® mixing valve without trim
- S-86-2-BODY-X.... Symmons Temptrol® mixing valve without trim. Valve includes integral service stops to allow water shut-off for service

#### Finish Options / Modifications

*Append appropriate -suffix to model number*

- Polished chrome (standard finish)

#### Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05

#### Options / Modifications

*Append appropriate -suffix to model number*

- X Symmons Temptrol mixing valve includes integral service stops to allow water shut-off for service, p/n S-86-2-BODY-X. *(Option only applies when ordering model S-2002)*
- IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve *(Not available on valves with integral service stops; option -X)*
- REV Reverse coring in valve for back to back installations; hot on right, cold on left, *(Only available on valves with integral service stops; option -X)*
- CHKS Check Stops: Temptrol® mixing valve includes integral check stops. *(Only available on valves with integral service stops; option -X)*
- 2.0 2.0 gpm (7.6 L/min) flow rate restrictor
- 1.5 1.5 gpm (5.7 L/min) flow rate restrictor
- RB Red blue colored indicators on escutcheon
- D Brass dome cover
- L/HD Showerhead not included, Mounting arm and flange are included
- SS Tub spout #061, 5-1/4" slip-on zinc spout instead of standard #060 tub spout

#### Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations

# Dimensions Symmetrix Tub-Shower System, S-2002

