Location:



ADACHS
ADA Hand Shower Wand
Specification Submittal



Model Numbers		Feature Highlights
☐ ADACH	S ADA Hand Shower Wand	 ADA hand shower wand features single mode spray Easy to operate non-positive shut-off button
Options/ Modifications		 Easy to clean rubber nozzles Standard 2.0 gpm (7.6 L/min) flow restrictor
☐ 1.5 C	1.5 gpm (5.7 L/min) flow restrictor	 Components made from metal and nonmetallic materials Plated in standard polished chrome finish
☐ 1.75 C	1.75 gpm (6.6 L/min) flow restrictor	
□ WHT	White finish	
□ МВ	Matte Black finish	
☐ STN	Satin Nickel finish	Warranty
□ ввz	Brushed Bronze finish	Limited Lifetime - to the original end
Note: Append appropriate -suffix to model number.		purchaser in consumer/residential installations.
Compliance		10 Years - for commercial/industrial
A CAME A 110 10 1 /CC A D10 E 1		installations. Refer to

Architectural/Engineering Specification

2.0 gpm (7.6 L/min)

Symmons ADA Hand Shower Wand ______ Includes ADA hand shower wand features single mode spray, Easy to operate non-positive shut-off button, Easy to clean rubber nozzles, Standard 2.0 gpm (7.6 L/min) flow restrictor, Components made from metal and nonmetallic materials, Plated in standard polished chrome finish. 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm (5.7 L/min), 2.0 gpm (7.6 L/min) compliant. Available options: "1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "1.75 - 1.75 gpm (6.6 L/min) flow restrictor", "WHT - White finish", "MB - Matte Black finish", "STN - Satin Nickel finish", "BBZ - Brushed Bronze finish".


www.symmons.com/warranty for

complete warranty information.

Dimensions

- ASME A112.18.1/CSA B125.1

- WaterSense 1.5 gpm (5.7 L/min)



Measurements		
Α	Ø 3-3/8", 85 mm	
В	7-7/8", 201 mm	
С	G 1/2", 13 mm	

Note: Dimensions subject to change without notice.