



SYMMONS® Allura®

Location:

4-143

Shower Head

Specification Submittal



Model Numbers

☐ **4-143** Shower Head

Options/ Modifications

- ☐ **1.5** 1.5 (5.7 L/min) Flow rate restrictor
- ☐ **1.75** 1.75 gpm (6.6 L/min) flow rate restrictor
- ☐ **STN** Satin Nickel finish

Note: Append appropriate -suffix to model number.

Compliance

- ASME A112.18.1/CSA B125.1
- 1.5, 1.75, and 2.0 GPM Shower Heads
meet WaterSense requirements




Feature Highlights

- Symmons Allura three mode shower head with full shower
- Pulsating massage and soft shower water saving spray
- Standard female ball joint connection
- Standard flow rate is 2.0 gpm (7.6 L/min)

Warranty

Limited Lifetime - to the original end purchaser in consumer/residential installations.

10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.



Architectural/ Engineering Specification

Symmons Allura Shower Head _____ Includes Symmons Allura three mode shower head with full shower, Pulsating massage and soft shower water saving spray, Standard female ball joint connection, Standard flow rate is 2.0 gpm (7.6 L/min). 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1, 1.5, 1.75, and 2.0 GPM Shower Heads meet WaterSense requirements compliant. Available options: "1.5 - 1.5 (5.7 L/min) Flow rate restrictor", "1.75 - 1.75 gpm (6.6 L/min) flow rate restrictor", "STN - Satin Nickel finish".

Dimensions

